



RELTECH

Where the water flows best...



Premium PR Series Pool & Spa Pump

- High Water Flow & Maximum Pressure
- Low Noise Operation & Energy Efficient
- Suitable For Residential And Commercial Swimming Pools And Spas
- Suitable For Swim Spas And Pools With In-Floor Cleaning
- 3 Year Limited Warranty

Australian Made

www.reltech.com.au

IMPROVEMENTS & ADVANCEMENTS

- Reltech's engineers have worked closely together to develop a pump that better handles the tough Australian climate. This has lead to improved reliability, efficiency and the overall performance of our pump.

DURABLE, RELIABLE, SAFE & DESIGNED TO LAST

- Strongly constructed thick walled, one piece pump body made from a high quality engineering grade thermoplastic material that is corrosion resistant. A glass reinforcement and UV additives also ensures the pump is designed to last in all weather conditions.
- Powerful and reliable motor rated for continuous operation ensures a long bearing life.
- Built in thermal overload protects the motor against damage from overheating.
- A stainless steel pump shaft, a lapped true carbon face, ceramic seal and stainless steel assembly nuts and bolts are just some of the quality components used to ensure ongoing reliability and extended lifecycle.
- Elevated motor stand assembled to main body prevents any warping under high water pressure, ensures balanced support for motor and pump, reduces noise and vibration and keeps moisture away from the motor.


POWERFUL, QUIET & ENERGY EFFICIENT

- The design characteristics of the diffuser and balanced impeller system ensures low noise operation whilst offering excellent priming. It also offers powerful water flow and filtration with maximum pressure at economical running costs.


USER FRIENDLY & FUNCTIONAL

- Extra large robust strainer basket prevents breakage during operation and debris removal and requires less frequent cleaning.
- Positively located strainer basket to eliminate the inlet being blocked.
- Easy removable clear inspection lid for quick and easy routine maintenance and cleaning of strainer basket.
- No stress on the sealing o-rings because clamping pressure is used rather than twisting pressure, therefore extending the life of spare parts on your pump.
- Self aligning inlet and outlet barrel unions for both suction and discharge ports allowing for quick and easy installation and removal.
- Barrel unions are suitable for both 40mm and 50mm PVC pipe connections.
- Premium PR Series is covered by a limited 3 year warranty against defects in materials and workmanship (refer to Operating + Installation Manual for full details).

PR SERIES PERFORMANCE CURVES



RELTECH PREMIUM PR SERIES MODEL	HP	FLOW RATE @ 8mtr HEAD	VOLTS / PHASE	FULL LOAD AMPS	WATTS INPUT	MAX NOISE dB(A) @ 1mtr	LENGTH OF PUMP (A)
PR 50	0.50	160	240 / 1	2.98	690	55	605
PR 75	0.75	190	240 / 1	3.60	850	58	625
PR 100	1.00	270	240 / 1	4.10	950	60	605
PR 125	1.25	330	240 / 1	4.97	1150	62	610
PR 150	1.50	380	240 / 1	6.40	1500	63	625
PR 200	2.00	490	240 / 1	8.60	1980	65	655



AVAILABLE FROM

